



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and
Regulation (EC) No. 1272/2008

Issuing Date 22-Aug-2024

Revision Date 22-Aug-2024

Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name White Lithium Spray Grease

Product Code(s) GSPSC

Synonyms None

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Spray grease

Uses advised against Use only for intended applications

1.3. Details of the supplier of the safety data sheet

Supplier

AMSOIL INC.
One AMSOIL Center
Superior, WI 54880, USA
T: +1 715-392-7101

For further information, please contact

E-mail address compliance@amsoil.com

1.4. Emergency telephone number

Emergency telephone CHEMTREC International: +1 703-741-5970

Emergency telephone - §45 - (EC)1272/2008

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 2 - (H223, H229)
Aspiration hazard	Category 1 - (H304)

2.2. Label elements



Signal word
Danger

Hazard statements

H304 - May be fatal if swallowed and enters airways.

H223 - Flammable aerosol.

H229 - Pressurised container: May burst if heated.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

18 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Additional information

This product is exempt from the requirement for a child resistant fastening and tactile warning of danger, as it is an aspiration hazard, placed on the market in the form of an aerosol or in a container with a sealed spray attachment.

2.3. Other hazards

Other hazards No information available.

PBT & vPvB None known

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Base oil 64742-01-4	30-50	No data available	265-101-6 (649-459-00-4)	Carc. 1B (*L) (H350)	-	-	-	L
Propane 74-98-6	5-15	No data available	200-827-9 (601-003-00-5)	Flam. Gas 1 (H220) Press. Gas	-	-	-	U
Butane 106-97-8	5-15	No data available	203-448-7 (601-004-00-0)	Flam. Gas 1 (H220) Press. Gas	-	-	-	C,U
Diethanolamine	0.1-1	No data	203-868-0	Acute Tox. 4 (H302)	-	-	-	-

111-42-2		available	(603-071-00-1)	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT RE 2 (H373)				
----------	--	-----------	----------------	---	--	--	--	--

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note L - The harmonized classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ('Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method' Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Base oil 64742-01-4	5000	2000	No data available	No data available	No data available
Propane 74-98-6	No data available	No data available	No data available	No data available	200000
Butane 106-97-8	No data available	No data available	No data available	No data available	276808.3276
Diethanolamine 111-42-2	780	13034.07	No data available	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. Take off contaminated clothing. Get medical attention if irritation develops and persists.

Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically. Symptoms may be delayed. Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
-----------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Use extinguishing agent suitable for type of surrounding fire.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
Hazardous combustion products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3. Advice for firefighters

Specific/special fire-fighting measures	Fires need to be assessed to determine appropriate protocols and safety measures for firefighting, including establishing safe zones, extinguishing media to be used, firefighter protection, and actions to control or extinguish the fire.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate
----------------------	---

ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections For additional information see: Section 8: Exposure controls/personal protection; Section 12: Ecological information; Section 13: Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture: Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Do not reuse empty containers. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials.

Storage class (TRGS 510) LGK 2B.

7.3. Specific end use(s)

Specific use(s).

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure Limits**

Under conditions which may generate mists, the following exposure limits are recommended: Long-term exposure limit (8-hour TWA): 5 mg/m³. Short-term exposure limit (15-minute): 10 mg/m³.

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Propane 74-98-6	-	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL 2000 ppm STEL 3600 mg/m ³	TWA: 1000 ppm	TWA: 1800.0 mg/m ³	-
Butane 106-97-8	-	TWA: 800 ppm TWA: 1900 mg/m ³ STEL 1600 ppm STEL 3800 mg/m ³	TWA: 1000 ppm STEL: 980 ppm STEL: 2370 mg/m ³	TWA: 1900 mg/m ³	TWA: 600 ppm TWA: 1450 mg/m ³ TWA: 10 ppm TWA: 22 mg/m ³ STEL: 750 ppm STEL: 1810 mg/m ³
Diethanolamine 111-42-2	-	TWA: 0.46 ppm TWA: 2 mg/m ³ STEL 0.92 ppm STEL 4 mg/m ³ Sk* Sh+	TWA: 0.2 ppm TWA: 1 mg/m ³ Sk*	TWA: 10 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³ Sk*
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
Propane 74-98-6	-	-	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 2000 ppm STEL: 3600 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³	TWA: 800 ppm TWA: 1500 mg/m ³ STEL: 1100 ppm STEL: 2000 mg/m ³
Butane 106-97-8	-	-	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³	TWA: 800 ppm TWA: 1500 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³
Diethanolamine 111-42-2	-	TWA: 5 mg/m ³ Ceiling: 10 mg/m ³	TWA: 0.46 ppm TWA: 2 mg/m ³ STEL: 0.92 ppm STEL: 4 mg/m ³ Sk*	TWA: 3 ppm TWA: 5 mg/m ³ STEL: 6 ppm STEL: 30 mg/m ³ Sk*	TWA: 0.46 ppm TWA: 2 mg/m ³ Sk*
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
Propane 74-98-6	-	TWA: 1000 ppm TWA: 1800 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³ Peak: 4000 ppm Peak: 7200 mg/m ³	TWA: 1000 ppm TWA: 1800 mg/m ³	-
Butane 106-97-8	TWA: 800 ppm TWA: 1900 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³ Peak: 4000 ppm Peak: 9600 mg/m ³	TWA: 1000 ppm TWA: 2350 mg/m ³	TWA: 2350 mg/m ³ STEL: 9400 mg/m ³
Diethanolamine 111-42-2	TWA: 3 ppm TWA: 15 mg/m ³	TWA: 0.11 ppm TWA: 0.5 mg/m ³ Sk* Sh+	TWA: 1 mg/m ³ Peak: 1 mg/m ³ Sk* skin sensitizer	TWA: 3 ppm TWA: 15 mg/m ³	-
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
Propane 74-98-6	STEL: 3000 ppm Simple asphyxiant	-	: Simple asphyxiant	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 300 mg/m ³	-

Butane 106-97-8	TWA: 1000 ppm STEL: 3000 ppm	-	STEL: 1000 ppm STEL: 2377 mg/m ³	TWA: 300 mg/m ³ STEL: 300 mg/m ³	-
Diethanolamine 111-42-2	TWA: 0.2 ppm TWA: 1 mg/m ³ STEL: 0.6 ppm STEL: 3 mg/m ³ Sk*	-	TWA: 1 mg/m ³ Sk*	-	TWA: 3 ppm TWA: 15 mg/m ³ STEL: 6 ppm STEL: 30 mg/m ³ Sk*
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
Propane 74-98-6	-	-	-	TWA: 500 ppm TWA: 900 mg/m ³ STEL: 625 ppm STEL: 1125 mg/m ³	TWA: 1800 mg/m ³
Butane 106-97-8	-	-	-	TWA: 250 ppm TWA: 600 mg/m ³ STEL: 312.5 ppm STEL: 750 mg/m ³	TWA: 1900 mg/m ³ STEL: 3000 mg/m ³
Diethanolamine 111-42-2	-	-	-	TWA: 3 ppm TWA: 15 mg/m ³ STEL: 6 ppm STEL: 22.5 mg/m ³	TWA: 9 mg/m ³ Sk*
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Propane 74-98-6	TWA: 1000 ppm	TWA: 778 ppm TWA: 1400 mg/m ³ STEL: 1000 ppm STEL: 1800 mg/m ³	-	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 4000 ppm STEL: 7200 mg/m ³	TWA: 1000 ppm
Butane 106-97-8	TWA: 1000 ppm STEL: 1000 ppm	TWA: 700 mg/m ³ STEL: 1000 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: 5000 ppm STEL: 12000 mg/m ³	TWA: 1000 ppm TWA: 2400 mg/m ³ STEL: 4000 ppm STEL: 9600 mg/m ³	TWA: 1000 ppm
Diethanolamine 111-42-2	TWA: 1 mg/m ³ Sk*	-	-	TWA: 0.5 mg/m ³ TWA: 0.11 ppm STEL: 0.11 ppm STEL: 0.5 mg/m ³ Sk*	TWA: 0.2 ppm TWA: 1 mg/m ³ Sk*
Chemical name	Sweden		Switzerland		United Kingdom
Propane 74-98-6	NGV: 350 mg/m ³		TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 4000 ppm STEL: 7200 mg/m ³		-
Butane 106-97-8	NGV: 350 mg/m ³		TWA: 800 ppm TWA: 1900 mg/m ³ STEL: 3200 ppm STEL: 7600 mg/m ³		TWA: 600 ppm TWA: 1450 mg/m ³ STEL: 750 ppm STEL: 1810 mg/m ³
Diethanolamine 111-42-2	NGV: 3 ppm NGV: 15 mg/m ³ Vägledande KGV: 6 ppm Vägledande KGV: 30 mg/m ³ Sk*		TWA: 1 mg/m ³ STEL: 1 mg/m ³ Sk* S+		-

Biological occupational exposure limits

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Base oil 64742-01-4	-	0.97 mg/kg bw/day [4] [6]	2.73 mg/m ³ [4] [6] 5.58 mg/m ³ [5] [6]
Diethanolamine	-	0.13 mg/kg bw/day [4] [6]	0.75 mg/m ³ [4] [6]

Chemical name	Oral	Dermal	Inhalation
111-42-2			0.5 mg/m ³ [5] [6]

Notes

[4]	Systemic health effects.
[5]	Local health effects.
[6]	Long term.

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
Base oil 64742-01-4	0.74 mg/kg bw/day [4] [6]	-	1.19 mg/m ³ [5] [6]
Diethanolamine 111-42-2	0.06 mg/kg bw/day [4] [6]	-	0.125 mg/m ³ [4] [6] 0.125 mg/m ³ [5] [6]

Notes

[4]	Systemic health effects.
[5]	Local health effects.
[6]	Long term.

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Diethanolamine 111-42-2	0.021 mg/L	0.095 mg/L	0.002 mg/L	-	-

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Base oil 64742-01-4	-	-	-	-	9.33 mg/kg food
Diethanolamine 111-42-2	0.092 mg/kg sediment dw	0.0092 mg/kg sediment dw	100 mg/L	1.63 mg/kg soil dw	1.04 mg/kg food

8.2. Exposure controls**Engineering controls**

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye/face protection**

If there is a risk of contact: Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures. Eye protection must conform to standard EN 166.

Hand protection

If there is a risk of contact: Wear suitable gloves. Impervious gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.

Skin and body protection

If there is a risk of contact: Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots. (EN ISO 6529).

Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.
Environmental exposure controls	Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid spray aerosol
Physical state	Aerosol
Colour	Clear / White
Odour	Mild hydrocarbon
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flammability		Level 2 Aerosol
Flammability Limit in Air		
Upper flammability or explosive limits	9.5%	No data available
Lower flammability or explosive limits	2.1%	No data available
Flash point	-104 °C	Propane
Autoignition temperature		No data available
Decomposition temperature		No data available
pH		No data available
pH (as aqueous solution)		No data available
Kinematic viscosity	< 20 cSt	@ 40 °C
Dynamic viscosity		No data available
Water solubility		No data available
Solubility(ies)		No data available
Partition coefficient		No data available
Vapour pressure	ca. 95 x 10 ⁻⁴	Propane
Relative density	2.1% - 9.5% v/v	Propane
Bulk density		No data available
Liquid Density		No data available
Relative vapour density	ca. 1.56 @ 0 °C	Propane
Particle characteristics		
Particle Size		No data available
Particle Size Distribution		No data available

9.2. Other information

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	None under normal use conditions.
-------------------	-----------------------------------

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Reacts with strong oxidizing agents.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. High temperature. Protect from direct sunlight. Containers may rupture or explode if exposed to heat.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition can lead to release of irritating and toxic gases and vapours. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Information on likely routes of exposure****Product Information**

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Specific test data for the substance or mixture is not available. Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (dermal) 2,762.76 mg/kg
ATEmix (inhalation-gas) 379,509.00 ppm

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Base oil 64742-01-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>20 mg/L (Rat) 4 h
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Diethanolamine 111-42-2	= 780 mg/kg (Rat)	= 11.9 mL/kg (Rabbit)	> 3.35 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	European Union
Butane	Muta. 1B

Carcinogenicity The supplier declares that it can be shown that the substance(s) contain less than 3% DMSO extract as measured by IP 346.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Base oil	Carc. 1B
Butane	Carc. 1A

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Base oil 64742-01-4	-	LC50: >5000mg/L (96h, <i>Oncorhynchus mykiss</i>)	-	EC50: >1000mg/L (48h, <i>Daphnia magna</i>)
Diethanolamine 111-42-2	EC50: =7.8mg/L (72h, <i>Desmodesmus subspicatus</i>) EC50: 2.1 - 2.3mg/L (96h, <i>Pseudokirchneriella subcapitata</i>)	LC50: 4460 - 4980mg/L (96h, <i>Pimephales promelas</i>) LC50: 1200 - 1580mg/L (96h, <i>Pimephales promelas</i>) LC50: 600 - 1000mg/L (96h, <i>Lepomis macrochirus</i>)	-	EC50: =55mg/L (48h, <i>Daphnia magna</i>)

12.2. Persistence and degradability**Persistence and degradability**

No information available.

12.3. Bioaccumulative potential**Bioaccumulation****Component Information**

Chemical name	Partition coefficient
Propane	1.09
Butane	2.31
Diethanolamine	-2.46

12.4. Mobility in soil**Mobility in soil**

No information available.

12.5. Results of PBT and vPvB assessment**PBT and vPvB assessment**

Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Base oil 64742-01-4	The substance is not PBT / vPvB
Propane 74-98-6	The substance is not PBT / vPvB
Butane 106-97-8	The substance is not PBT / vPvB
Diethanolamine 111-42-2	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties**Endocrine disrupting properties**

Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects	No information available.
PMT or vPvM properties	Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Waste codes / waste designations according to EWC / AVV	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information**IATA**

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not applicable
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	No
14.6 Special Precautions for Users	
Special Provisions	A145, A167, A802
ERG Code	10L
Note:	None

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not applicable
Description	UN1950, Aerosols, 2.1
14.5 Environmental hazards	No
14.6 Special Precautions for Users	
Special Provisions	63,190, 277, 327, 344, 381, 959
EmS-No.	F-D S-U
14.7 Maritime transport in bulk according to IMO instruments	No information available

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not applicable
Description	UN1950, AEROSOLS, 2.1
14.5 Environmental hazards	No
14.6 Special Precautions for Users	
Special Provisions	190, 327, 344, 625
Classification code	5F

ADR

14.1 UN number or ID number	UN1950
-----------------------------	--------

14.2 UN proper shipping name	AEROSOLS
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not applicable
Description	UN1950, AEROSOLS, 2.1
14.5 Environmental hazards	No
14.6 Special Precautions for Users	
Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)

ADN

14.1 UN/ID no	UN1950
14.2 EPNN	AEROSOLS
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not applicable
Description	UN1950, AEROSOLS, 2.1
14.5 Environmental hazard	No
14.6 Special Precautions for Users	
Special Provisions	190, 327, 344, 625
Classification code	5F
Ventilation	VE01, VE04
Equipment Requirements	PP, EX, A

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations****France****Occupational Illnesses (R-463-3, France)**

Chemical name	French RG number
Diethanolamine 111-42-2	RG 49, RG 49bis

Germany

Water hazard class (WGK) strongly hazardous to water (WGK 3)

Switzerland

Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC) SR 814.018 Group I
WPO (GSchV) SR 814.201; WPA (GSchG) SR 814.20 Class B

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Base oil - 64742-01-4	28 75	-
Butane - 106-97-8	28 29 75	-
Diethanolamine - 111-42-2	75	-

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

Contact supplier for inventory compliance status

15.2. Chemical safety assessment**Chemical Safety Report**

No information available

SECTION 16: Other information**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

H220 - Extremely flammable gas

H302 - Harmful if swallowed

H315 - Causes skin irritation

H318 - Causes serious eye damage

H350 - May cause cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

Sk*

Skin designation

SCBA Self-contained breathing apparatus

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method

Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	On basis of test data
Carcinogenicity	On basis of test data
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	On basis of test data
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
 European Chemicals Agency (ECHA) (ECHA_API)
 Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan GHS Classification
 Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
 Organisation for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Issuing Date 22-Aug-2024

Revision Date 22-Aug-2024

Revision Note Initial Release.

This safety data sheet complies with the requirements of Commission Regulation (EU) 2020/878 of 18 June 2020 amending Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet